

WOODline

Parquet on system floors

WOODline parquet flooring consists of 4 mm thick solid wood top layers, which are factory-bonded to either raised floor panels (LIGNA / NORTEC) or dry hollow floor panels (FLOOR and more®). The top layer is available in all common wood types and designs, can be coated with either lacquer or oil and is protected by color-coordinated edge protection when applied to raised floor panels.

The uniform appearance, factory application and on-site surface treatment enable quick, cost-effective installation and seamless combination of both flooring systems.

This product data sheet is only valid in conjunction with the product data sheet of the respective floor panel!

- Parquet layers from our own production with highest quality
- Certification according to FSC™ possible
- Combination possibilities with our raised floors and boarded parquet "Gallery board"
- Combination possibilities with our industrial design planks
- Real wood layer
- Further types of wood and designs upon request



Technical details






Thickness		4.0 mm
Length		600 mm
Width		600 mm









Surface

standard lacquered	
Build-up	6-layer UV-curing lacquer structure
Carrier panel	NORTEC, LIGNA
Variants	lacquered colourless
Gloss level	matt
Slip resistance class	R9
Durability	Class 6
Building class EN 13501-1	C _{fl} -s1 (NORTEC)
Air Comfort Gold	fulfilled
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo ecru, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots
special lacquered	
Build-up	7-layer UV-curing lacquer structure
Carrier panel	NORTEC, LIGNA
Variants	lacquered colourless
Gloss level	matt
Durability	Class 6
Building class EN 13501-1	C _{fl} -s1 (NORTEC)
Air Comfort Gold	fulfilled
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo ecru, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots
oiled	
Build-up	two times hard wax oiled
Carrier panel	NORTEC, LIGNA
Gloss level	matt
Slip resistance class	R9
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo ecru, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots

pre-sanded	
Surface	Pre-sanded; Contamination/Traces caused by the application onto the carrier panel have to be factored in and have to be accepted
Carrier panel	NORTEC, LIGNA, FLOOR and more®
Utilisation	Surface coating to be done on site; Cleaning by sanding is mandatorily necessary
Types of wood	Oak, Oak smoked, Ash Eco, Bamboo ecru, Bamboo steamed
Wood grading	We use a wood grading with typical structure and play of colours, partly containing small sound knots
Note	The coating has to be carried out immediately after installation. We do not take responsibility for damages caused by incorrect storage. The used surface tools have to be approved by the manufacturer. Danger of edges sticking together. If necessary, consult with Product Management Flooring.

Designs

Large baton 4 (Oak)	Large baton 6 (Oak)	Large baton 8 (Oak)	Large baton 9 (Oak)
			
Industrial 3-18 (Oak)	Industrial 3-14 (Oak)	Industrial 3-10 (Oak)	Industrial 4-10 (Oak)
			
3-strip 9 (Oak)	2-strip (Oak)	Cube 81 (Oak)	Herringbone (Oak)
			

Mosaic 4 (Oak)	Mosaic 9 (Oak)	Mosaic 16 (Oak)	Industrial 4-18 (Ash)
			
Industrial 4-14 (Ash)	Industrial 3-18 (Bamboo)	FineLine (Bamboo)	Wide lamella (Bamboo)
			

The designs shown above are possible in all types of wood, except bamboo. Bamboo is only possible in the three designs shown.